

FusionServer

2488H V6 Server



FusionServer


2488H V6 Server



2488H V6

| Mission-critical Servers,
Stable and Reliable |

FusionServer 2488H V6 is the latest 2U 4-socket rack server. It is ideal for computing-intensive scenarios, such as cloud computing, virtualization, HPC, databases, and SAP HANA. Compared with two 2U 2-socket rack servers, the 2488H V6 saves more OPEX in virtualization scenarios. It is configured with four 3rd Intel® Xeon® Scalable processors and supports up to 48 DDR4 DIMMs, 11 PCIe slots and a maximum of 25 x 2.5-inch drives for local storage. It incorporates patented technologies, such as DMT and FDM, and integrates FusionDirector software for entire-lifecycle management, helping customers drive down OPEX and improve ROI.




Optimal Performance and High Efficiency

- Four 3rd generation Intel® Xeon® Scalable processors run on a 2U space. Each processor supports up to 28 computing cores. It supports Intel® Turbo Boost, hyper-threading, and AVX-512, improving server processing performance through six 10.4 GT/s UPI links.
- Supports Intel® Deep Learning Boost. The latest BFloat16 instruction set and vector neural network instructions (VNNI) provide up to 93% higher training and 90% higher inference performance than the previous generation processors FP32.
- Supports a maximum of 48 DDR4 DIMMs of the 3200 MT/s registered DIMMs (RDIMMs) and load-reduced DIMMs (LRDIMMs). The memory capacity is up to 12 TB, meeting the requirements of large-capacity memory applications.
- Supports the use of 24 Optane™ PMem 200 series with DDR4 DIMMs. The memory capacity is up to 18 TB to meet the demands of various workloads.
- Supports two dual-slot FHFL or four single-slot HHHH GPU heterogeneous accelerator cards, providing powerful computing power for AI analysis and training scenarios.
- Supports a maximum of 25 x 2.5-inch SAS/SATA drives and 16 NVMe SSDs. Multiple storage media can be combined to achieve data tiering and ultimate performance.
- Supports boot speedup storage technology (BSST). The OS is installed on two M.2 SSDs, which is deployed separately from service data. Supports hardware RAID and hot swappable for M.2 SSDs.



Smart Power Saving and Better Energy Efficiency

- Adopts DMT, driving down overall equipment power consumption by up to 15% without compromising workload performance through multiple power-saving measures such as component hibernation, PID/DTS algorithm based fan speed tuning, and active-standby power supplies.
- Supports 900 W, 1200 W, 1500 W, 2000 W and 3000 W PSU options, meeting various workloads and high performance requirements.
- Supports 1500 W HVDC PSUs, improving more than 94% energy efficiency.
- Uses 80 PLUS® Titanium PSUs that provide a conversion efficiency of up to 96%.



Intelligent Management and Openness for Integration

- Integrates FusionDirector for intelligent full-lifecycle O&M, improving O&M efficiency by 30%.
 - » Intelligent maintenance integrates diagnosis and recovery, and accurately manages key components. The fault diagnosis accuracy reaches 93% and the breakdown rate decreases by 50%.
 - » Intelligent upgrade enables one-click automation, cloud-based collaboration for quick policy formulation, and firmware versions automatic completeness and upgrade in batches, improving efficiency by 20x.
 - » Intelligent discovery enables 100% accuracy of component-level visualization, automatic asset inventorying in seconds, and real-time track tracing.
 - » Intelligent energy saving enables refined dynamic energy management. It integrates the DMT 2.0, saving 18% of the system energy.
 - » Intelligent deployment enables pipelined deployment and one-clicks switchover on demand, improving deployment efficiency by 10x.
- Provides standardized open interfaces and development guides, facilitating seamless integration with third-party management software.

FusionServer

2488H V6 Server

Server Type	2U rack server
Processors	Two or four 3rd Gen Intel® Xeon® scalable processors (5300/6300/8300 series), TDP up to 250 W
Chipset	Intel C621A
Memory	48 DDR4 DIMMss, up to 3,200 MT/s; 24 Optane™ PMem 200 series, up to 2,666 MT/s.
Local Storage	<p>Supports various drive configurations and hot swappable:</p> <ul style="list-style-type: none"> • 8 x 2.5-inch front SAS/SATA/NVME drives • 24 x 2.5-inch front SAS/SATA drives • 25 x 2.5-inch front SAS/SATA drives • 4 x 2.5-inch front SAS/SATA drives and 8 x NVMe SSDs • 4 x 2.5-inch front SAS/SATA drives and 16 x NVMe SSDs <p>Supports flash storage:</p> <ul style="list-style-type: none"> • Dual M.2 SSDs
RAID Support	Supports RAID 0, 1, 10, 5, 50, 6, or 60, optional supercapacitor for cache data power failure protection, RAID level migration, drive roaming, self-diagnosis, and remote web-based configuration.
Network	(Optional) One OCP 3.0 NIC: supports two GE, two 10GE, two 25GE, or two 100GE ports; supports hot-swappable, NC-SI, WOL, and PXE.
PCIe Expansion	Provides up to 11 PCIe 3.0 slots, including 9 rear I/O PCIe slots, 1 internal PCIe slot, and 1 OCP 3.0-dedicated FlexIO slot
Heterogeneous Acceleration Cards	Supports two dual-slot FHFL GPUs or four single-slot HHHL GPU heterogeneous accelerator cards. For details, see https://www.xfusion.com/en/
Fan Modules	Six hot-swappable fan modules in N+1 redundancy mode
Power Supply	<p>Two hot-swappable PSUs in 1+1 redundancy mode. Supported options include:</p> <ul style="list-style-type: none"> • 3000 W AC Titanium PSUs <ul style="list-style-type: none"> 2500 W (input: 200 V to 220 V AC) 2900 W (input: 220 V to 230 V AC) 3000 W (input: 230 V to 240 V AC) • 2000 W AC Platinum PSUs <ul style="list-style-type: none"> 1800 W (input: 200 V to 220 V AC, or 192 V to 200 V DC) 2000 W (input: 220 V to 240 V AC, or 200 V to 288 V DC) • 900 W AC Platinum/Titanium PSUs (input: 100 V to 240 V AC, or 192 V to 288 V DC) • 1500 W HVDC PSUs (input: 260 V to 400 V DC, or 200 V to 277 V AC) • 1200 W DC PSUs (input: -38.4 V to -72 V DC)
Management	<p>The iBMC chip integrates one dedicated GE management port to provide comprehensive management functions such as fault diagnosis, automated O&M, and hardware security hardening.</p> <ul style="list-style-type: none"> • The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0; provides a remote management user interface based on HTML5/VNC KVM; supports CD-free deployment and Agentless for smart and simplified management. • (Optional) Configured with the FusionDirector management software to provide advanced management functions such as stateless computing, batch OS deployment, and automated firmware upgrade, enabling automatic management throughout the lifecycle.
Operating Systems	Microsoft Windows Server, SUSE Linux Enterprise Server VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, Debian, etc. For details, see https://www.xfusion.com/en/
Security Features	Supports power-on password, administrator password, Trusted Cryptography Module (TCM) /TPM 2.0, security panel, secure boot, and cover opening detection.
Operating Temperature	5°C to 45°C (41°F to 113°F) (ASHRAE Class A1/A2/A3/A4 compliant)
Certifications	CE, UL, FCC, CCC, RoHS, etc
Installation Kit	Supports adjustable guide rails, holding rails, and cable management arm.
Dimensions (H x W x D)	86.1 mm x 447 mm x 790 mm (3.39 in. x 17.60 in. x 31.10in.)

xFusion Digital Technologies Co., Ltd.

Consulting telephone: 400-080-6888 Technical hotline: 400-009-8999

Address: 9th Floor, Building 1, Zensun Boya Square, Longzihu Wisdom Island,
Zhengdong New District, Zhengzhou, Henan Province

Address: www.xfusion.com

Copyrights © xFusion Digital Technologies Co., Ltd 2022. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of xFusion Digital Technologies Co., Ltd.

Trademarks and Permissions

XFUSION and other xFusion trademarks are trademarks of xFusion Digital Technologies Co., Ltd. All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

In this document, "xFusion" is used to refer to "xFusion Digital Technologies Co., Ltd." for concise description and easy understanding, which does not mean that "xFusion" may have any other meaning. Any "xFusion" mentioned or described hereof may not be understood as any meaning other than "xFusion Digital Technologies Co., Ltd.", and xFusion Digital Technology Co., Ltd. shall not bear any liability resulting from the use of "xFusion".

The purchased products, services and features are stipulated by the contract made between xFusion and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.